



DC Input Servo

Product Catalogue

Reliable Motion Control Partner


• Page Index	01-08
Company Profile Product System Servo Product Servo Products Quick Selection Typical Industry Applications	
• DC Servo Drive	09-26
ELD2 Series Servo Drives • ELD2 • 2ELD2 ELD3 Series Servo Drives • ELD3	
• Integrated Servo Motors	27-31
iSV2 Series Integrated Servo Motors • iSV2 Series	
• Servo Motors	32-51
ELVM Series Cable Selection	

Leadshine Servo Products Quick Selection

Servo Drive	Model	Power (W)	Main Voltage (VDC)	Logic Power (VDC)	Dimensions (mm)	Weight (kg)		Command Source		Command Source			STO	Encoder Output	Brake Output	Digital Inputs	Digital Outputs	Analog Inputs	Matched Servo Motors		
								Pulse+Dir	Analog	RS485	EtherCAT	CANopen									
DC Servo Drive Single-Axis ELD2 Series	ELD2-RS7005	200	24-70	-	118*75.5*25.5	0.2		√	√	√						4	2		*ELVM Servo Motors for more information please refer to pages 50 to 51 *3rd Party Brushless / Brushed Motor		
	ELD2-CAN7005B				140*79.5*25.5	0.3						√			√	4	2				
	ELD2-RS7010	400			118*75.5*25.5	0.2		√	√	√				√		4	2				
	ELD2-CAN7010B				140*79.5*25.5	0.3						√		√	√	4	2				

2ELD2-**7020/7030B

Unit: mm



Specifications

2ELD2 series	2ELD2-RS7020B 2ELD2-CAN7020B	2ELD2-RS7030B 2ELD2-CAN7030B
Rated Current (Arms)	20	30
Peak Current (Arms)	57	64
Main power supply	24 ~ 70VDC	
Direct Drive Holding Brake	Yes	
Drive mode	SVPWM sinusoidal wave drive	
Velocity regulation ratio	5000:1	
Electronic gear ratio	1 ~ 32767/1 ~ 32767	
Matching encoders	Hall signal UVW + ABZ or RS485 encoder (Tamagawa protocol)	
Analog Input	2 analog inputs (AI1/AI2), -10V~+10V, Max. voltage : ±12V - CAN models	
Digital Input	2 pulse differential 5V Digital input (Pulse+direction) - RS models 4 configurable NPN/PNP 24V Digital Inputs	

Part Numbers

ELVM - 60 20 V48 E - H - M17 - HD

(1)

(2)

(3)

(4)

(5)

(6)

(7)

(8)

(1) Series Num

ELVM ELVM Series servo motor

(2) Frame Size

25	25mm
40	40mm
60	60mm
80	80mm
130	130mm

(3) Rated Output Power

03	33W	05	50W
10	100W	20	200W
40	400W	60	600W
75	750W	100	1000W
120	1200W	150	1500W
200	2000W		

(4) Voltage

V24	24V
V36	36V
V48	48V
V60	60V

(8) Connect type

Blank	Direct connector
HD	Aviation connector-HD

(7) Encoder Type</

Motor cable model number

CABLE RZS H 3M0 - 1 1 3 - T - R

Sign	Meaning
CABLE	Cable identification

Sign	Cable type
RZ	Without brake motor cable
RZS	With brake motor cable

Sign	Voltage
H	AC Servo motor cable
D	DC Servo motor cable

Sign	Length	Sign	Length
1M5	1.5 meter	13M0	13 meter
3M0	3 meter	15M0	15 meter
5M0	5 meter	***	Please contact leadshine teams for other lengths
7M0	7 meter		
10M0	10 meter		

Sign	Drive side terminal type
1	Wire ferrule
2	Spade terminal

Sign	Customized models
R	Direct plug for backfacing wiring
***	Customized

Sign	Special requirements
Blank	Fixed cable
T	Flexible cable
TS	Flexible & oil proof cable
***	Reserved

Sign	Motor side terminal type
1	AMP plastic plug
2	Reserved
3	Assembly type aviation plug
4	Terminal type direct plug
***	Reserved

Sign	Cable specifications	Sign	Cable specifications
1	20AWG	5	14AWG
2	18AWG	6	12AWG
3	16AWG	7	19AW



Distributori
Advantech
per l’Italia

00390521694164
www.erre1.it
E-commerce: www.syby.it
info@erre1.it
Via Novella 13, 43058 Sorbolo, PR, Italy

ELVM-B25 Series

Type Name ELVM Series	Matched Drive		Matched Cable			
	CANopen	RS485	Motor Cable	Motor +Brake Cable	Encoder Cable	Brake Cable
4005V48EH-B25-HD	ELD2-CAN7005B	ELD2-RS7005	/	CABLE-RZSD*M*-123	CABLE-LD2-BM*M* (Single-turn)	/
4005V48FH-B25-HD			CABLE-RZD*M*-123	/		
4010V48EH-B25-HD			/	CABLE-RZSD*M*-123		
4010V48FH-B25-HD			CABLE-RZD*M*-123	/		
6020V24EH-B25-HD	ELD2-CAN7010B	ELD2-RS7010	CABLE-RZD*M*-143	/		CABLE-SCD*M*-113
6020V24FH-B25-HD			CABLE-RZD*M*-123	/		/
6020V48EH-B25-HD				/		